

TELSTAR DOORS

Engineered for the Modular Building Industry

SPECIFICATIONS TELSTAR PRO 3068 TELSTAR PRO 3070

The Telstar Doors are a pre-assembled 20 gauge hollow metal door and 16 gauge frame with exterior surface flange to fit your modular building needs. Our doors are manufactured from high quality galvannealed steel with a polystyrene core and come factory assembled.

ILLS IAK FRO 3000	ILLS IAK FRO 3070	ILLSTAN
35 ¾" x 79 ½" x 1 ¾"	35 ¾" x 83 ½" x 1 ¾"	34 ¾" x 78 ½" x 1 ¾"
38" x 81"	38" x 85"	36" x 80"
40 ½" x 82 ½	40 1/4" x 86 1/8"	38 5%" x 81 5/16"
32 1/4" w/o threshold flashing	82 1/4" w/o threshold flashing	82 1/4" w/o threshold flashing
37 ¼" x 80 %"	37 ¼" x 84 5%"	35 5/8" x 79 ¹³ /16"
TELSTAR PRO 6068	TELSTAR PRO 6070	
TELSTAR PRO 6068 35 3/4" x 79 1/8" x 1 3/4"	TELSTAR PRO 6070 35 3/4" x 83 1/8" x 1 3/4"	
35 ³ / ₄ " x 79 ½" x 1 ³ / ₄ "	35 ³ / ₄ " x 83 ¹ / ₈ " x 1 ³ / ₄ "	
3	8" x 81" 0 ½" x 82 ½ 2 ½" w/o threshold flashing	8" x 81" 38" x 85" 0 ¼" x 82 ½ 40 ¼" x 86 ½" 2 ¼" w/o threshold flashing 82 ¼" w/o threshold flashing

FEATURES	
Assembly	Pre-hung door and frame
Door	• 20 gauge galvannealed
Frame	16 gauge galvannealedWelded top cornersASA strike prep
Door Prep	161 lock with deadbolt prep
Hinge Prep	4½" heavy-duty hingesNon-removable hinge pin
Closer Prep	14 gauge reinforced steel, standard
Threshold	ADA compliant threshold, sweep and sealFlashing detaches for optional installation
Channels	16 gauge inverted top and bottom channel
Insulation	Polystyrene core
Paint	 Off white Bright White Medium Gray Prime
Shipping	• In crates of 8

Lock hardware and lite kits are additional.

PAINT OPTIONS







Other door & frame sizes available

