

Standard-Duty Grade 2 Indicator

DB2070 SERIES



FEATURES

- Performance**
- Complies with ANSI A156.5, Grade 2, 150,000 cycles
 - ULC listed
 - 3 hour fire rating
 - Complies with ADA

- Chassis**
- Tubular, steel

- Deadbolt**
- 1" x 2 1/4", square corner faceplate
 - 1" throw (solid brass with hardened steel rod insert)
 - Standard thumbturn

- Backset**
- Adjustable 2 3/8" to 2 3/4"

- Strike**
- 1 1/8" x 2 3/4", square corner faceplate

- Door Thickness**
- 1 3/8" - 2"

- Door Preparation**
- 2 1/8" diameter for bore
 - 1" diameter for bolt
 - Fits standard 161 door prep

- Warranty**
- Lifetime limited

Standard-Duty Grade 2 Indicator

DB2070 SERIES

ACCESSORIES


DRIVE-IN LATCH

CL100177 – 2 3/4" Guarded, US26D

Drive-in latch, adjustable..



FUNCTION CHART

OUTSIDE	INSIDE	FUNCTION	FEATURES	ANSI
		Double Cylinder 41	• Deadbolt operated by key outside, key inside	E0141
		Single Cylinder 51	• Deadbolt operated by key outside, thumb turn inside	E0151
		Single Cylinder Heavy Duty 51HD	• Deadbolt operated by key outside, thumb turn inside	E0152

OUTSIDE	INSIDE	FUNCTION	FEATURES	ANSI
		Communicating 25	• Deadbolt operated by inside, thumb turn only	E0162
		Communicating with Backplate K25	• Deadbolt operated by inside, thumb turn only with backplate	E0162

COMMERCIAL DOORS & HARDWARE | 800.433.4047 | tellmfg.com