

Light-Duty Grade 3 Tubular  
**DB3000 SERIES**



DB3051 – Single Cylinder

**FEATURES**

**Chassis** ▪ Tubular, steel — coated with zinc dichromate (corrosion resistance)

**Deadbolt** ▪ 1" x 2 ¼", square corner faceplate  
▪ 7/8" housing diameter  
▪ 1" throw  
▪ Anti-saw roller bar (for added security)

**Backset** ▪ Adjustable 2 3/8" or 2 3/4". 2 ¼" x 1" faceplate standard  
▪ Drive-in optional.

**Strike** ▪ 1" x 2 ¼", square corner faceplate

**Cylinder** ▪ C keyway (SCC)  
▪ 6-pin solid brass  
▪ Keyed different (KD)

**Keys** ▪ Two nickel silver per lock cylinder (Two per deadbolt)

**Door Thickness** ▪ 1 3/8" - 1 3/4"

**Door Preparation** ▪ 2 1/8" diameter for bore  
▪ 1" diameter for bolt  
▪ Fits standard 161 door prep

**Warranty** ▪ Limited lifetime

# DB3000 SERIES

## OPTIONS

<b>Keying</b>	6-pin cylinders, can be pinned to 5-pin.
<b>Cylinders</b>	Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Options Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)
<b>IC Keyway Cylinders Available 6- or 7-Pin</b>	Best A (BA), Best B (BB), Best C (BC), Best D (BD), Best E (BE), Best F (BF), Best G (BG), Best H (BH), Best J (BJ), Best K (BK), Best L (BL), Best M (BM), Best Q (BQ), Best U (BU), Black construction core (BLK), Less core (00), Not specified (XX)
<b>Keying Options</b>	Grand Master Key (GMK), Construction Master Key (CMK), Master Key (MK), Keyed Different (KD), Keyed Alike (KA), Interchangeable Core uncombined (IC), 0-bitted (0BIT)
<b>Available Functions</b>	Double Cylinder 3041 Single Cylinder 3051

### Tell Finishes



US3  
Polished Brass



US15  
Satin Nickel



US19  
Matte Black