

# KNOCKDOWN COMMERCIAL DOORS



## STANDARD FEATURES:

- Insulated with Polystyrene Core
- Galvannealed (Standard)
- 7 Gauge Hinge Reinforcements
- Reinforced 161 Lock Prep
- Meets Ansi Standards
- Universal 4 1/2" Hinge Prep
- Inverted Top and Bottom Channel
- Installed Steel Cap Standard



Preassembled  
doors are  
available, ask  
for details.



Size	Description
<b>3070</b>	Knockdown In White or Bronze
<b>4070</b>	Knockdown In White or Bronze
<b>6070</b>	Knockdown In White or Bronze

WIND RATED/FLORIDA APPROVED MEMBER: MBMA | MBCEA

## TIOGA DOOR SYSTEM | Engineered for the Metal Building Industry

Tell Manufacturing offers a line of commercial hollow metal doors to fit your metal building needs. Our knockdown doors are available in 20 and 18 gauge steel. All doors come with a polystyrene core as standard, making every door smoother, flatter, and stronger. All door panels are manufactured from high quality galvanized steel and are thoroughly cleaned inside and out to insure excellent corrosion resistance and paint adhesion. The doors come standard in white or bronze primed finish.

Tioga Doors can be wind rated or fire rated and follows the performance specifications set by the Steel Door Institute (SDI) requirements.



### TIOGA KNOCKDOWN COMPONENTS

#### DOOR

- 1-3/4" thick, 20 or 18 gauge steel, textured standard, smooth skin option
- Non-handed
- Galvanized
- Insulated with Polystyrene Core
- 7 gauge hinge reinforcements
- Reinforced 161 lock prep
- Universal 4-1/2" hinge prep
- Baked on rust inhibiting white or bronze primed finish
- 18 gauge top and bottom inverted channels
- Installed steel cap at top
- Meets ANSI standards

#### DOOR FRAME

- 16 gauge
- Galvanized
- 7 gauge hinge reinforcements
- Heavy duty 12 gauge reinforced strike plate prep
- Universal 4-1/2" hinge prep
- Baked on rust inhibiting white or bronze primed finish
- Meets ANSI standards
- Corners are bolted


#### LOCKSET *(optional, not included)*

- Standard duty, cylindrical grade 2
- Standard solid brass 6-pin cylinder with a Schlage C keyway
- 2-3/4" backset
- Chassis is steel and coated with corrosion resistant zinc dichromate



#### DOOR CLOSER *(optional, not included)*

- Standard duty, grade 1
- Adjustable back check, and sweep and latch speeds
- Door range up to 180°



#### HINGES

- 4-1/2" x 4-1/2" square corner
- Standard primed
- Non-removable pin



#### WEATHERSTRIPPING

- Kerfed and friction fitted



#### THRESHOLD

- 5" aluminum
- 1/2" saddle shaped that meets ADA



#### SWEEP

- Surface mounted
- Adjustable



OPTIONAL HARDWARE

HEAVY DUTY MORTISE LEVER, DEADBOLT, EXIT DEVICE, AND LITE KITS



Tell Manufacturing  
18 Richard Drive  
Lititz, PA 17543